



Auto Refinishing Products

Page 1/13

Printing date: 14.03.2022

Revision date: 14.03.2022

Version no. 1

Safety Data Sheet
according to WHS Regulations

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· Product identifier

· **Trade name:** **BODY F217 FIBERLIGHT POLYESTER FILLER**

· **Article number:** 792

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9b Fillers, putties, plasters, modelling clay

· **Process category** PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

· **Environmental release category** ERC2 Formulation into mixture

· **Article category** AC1 Vehicles

· **Application of the substance / the mixture** Surface protection

· Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

Sydney Automotive Paints & Equipment PTY LTD

Unit A3, 366 Edgar St. Condell Park NSW 2200

AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001

· **Emergency telephone number:**

If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zeland 0800 764 766.

AU

Continue on page 2

Trade name: **BODY F217 FIBERLIGHT POLYESTER FILLER**

2 Hazard(s) Identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Muta. 1A H340 May cause genetic defects.
Carc. 1A H350 May cause cancer.
Repr. 2 H361d Suspected of damaging the unborn child.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irritation 2A H319 Causes serious eye irritation.
STOT SE 3 H335 May cause respiratory irritation.

· Label elements

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02



GHS07



GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

styrene
isobutane

· **Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H361d Suspected of damaging the unborn child.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.








Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER**Other hazards****Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition and Information on Ingredients**Chemical characterisation: Mixtures**

- **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 100-42-5	styrene	20-<25%
EINECS: 202-851-5	 Flam. Liq. 3, H226	
Index number: 601-026-00-0	 Carc. 2, H351; Repr. 2, H361d; STOT RE 2, H373	
RTECS: WL 3675000	 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irritation 2A, H319; STOT SE 3, H335	
CAS: 25214-39-5	copolymer	1-<5%
	 Flam. Liq. 2, H225	
CAS: 75-28-5	isobutane	≥0.1-<0.9%
EINECS: 200-857-2	 Flam. Gas 1, H220	
Index number: 601-004-00-0	 Press. Gas C, H280	
RTECS: TZ 4300000	 Muta. 1A, H340; Carc. 1A, H350	

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures**Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

- **After swallowing:** If symptoms persist consult doctor.

Information for doctor:

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire Fighting Measures**Extinguishing media**

- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products

- **Special protective equipment and fire fighting procedures:** Mouth respiratory protective device.

Continue on page 4

AU

Trade name: **BODY F217 FIBERLIGHT POLYESTER FILLER**

- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

* 6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
 Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

* 7 Handling and Storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls and personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
 - **Control parameters**
 - **Ingredients with limit values that require monitoring at the workplace:**
-
- 100-42-5 styrene
 WES Short-term value: 426 mg/m³, 100 ppm
 Long-term value: 213 mg/m³, 50 ppm
- **Additional information:** The lists valid during the making were used as basis.
 - **Exposure controls**
 - **Personal protective equipment:**
 - **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER

Store protective clothing separately.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

* 9 Physical and Chemical Properties

· Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

Form:	Pasty
Colour:	Dark green
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.

· **Change in condition**

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	145.2 °C

· **Flash point:** 23 - 60 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 480 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

Continue on page 6

AU

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER

- **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.
- **Explosion limits:**
 - Lower:** 1.2 Vol %
 - Upper:** 8.9 Vol %
- **Vapour pressure at 20 °C:** 6 hPa
- **Density at 20 °C:** 1.15 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 22.9 %
 - VOC (EC)** 266.8 g/l
 - Solids content (volume):** 76.4 %
- **Other information** No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral LD50 21,879 mg/kg (rat)

Inhalative LC50/4 h 105 mg/l (rat)

100-42-5 styrene

Oral LD50 5,000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Irritant to skin and mucous membranes.

Continue on page 7

AU

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER

- **Serious eye damage/irritation** Irritating effect.
- **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
Muta. 1A, Carc. 1A, Repr. 2

12 Ecological Information

- **Toxicity**
- **Aquatic toxicity:**
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea
- **Persistence and degradability**
This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **ADG, IMDG, IATA** UN1263
- **UN proper shipping name**
- **ADG** UN1263 PAINT
- **IMDG, IATA** PAINT

Continue on page 8
AU

Trade name: **BODY F217 FIBERLIGHT POLYESTER FILLER**

· Transport hazard class(es)

· **ADG**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· Packing group

· **ADG, IMDG, IATA**

III

· Environmental hazards:

· **Marine pollutant:**

No

· Special precautions for user

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

30

· **EMS Number:**

F-E,S-E

· **Stowage Category**

A

· Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· **ADG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· **Transport category**

3

· **Tunnel restriction code**

D/E

· **IMDG**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III

* 15 Regulatory information

·3Y

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER**Australian Inventory of Industrial Chemicals**

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)
 100-42-5 styrene
 65997-17-3 Fibrous Glass
 25214-39-5 copolymer
 60676-86-0 Silica, fused
 75-28-5 isobutane
 75-35-4 1,1-dichloroethylene
 107-13-1 acrylonitrile

Standard for the Uniform Scheduling of Medicines and Poisons

100-42-5 styrene: S5
 107-13-1 acrylonitrile: S7

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

GHS02 GHS07 GHS08

· **Signal word** Danger

Hazard-determining components of labelling:

styrene
 isobutane

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H340 May cause genetic defects.
 H350 May cause cancer.
 H361d Suspected of damaging the unborn child.
 H335 May cause respiratory irritation.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER**· National regulations:****· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has been carried out.

*** 16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

· Contact:

HB BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033
email: stamkou@hbbody.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1: Flammable gases – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Muta. 1A: Germ cell mutagenicity – Category 1A
Carc. 1A: Carcinogenicity – Category 1A
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Continue on page 11
AU

Trade name: **BODY F217 FIBERLIGHT POLYESTER FILLER**

· * **Data compared to the previous version altered.**

AU
Continue on page 12

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER**Annex: Exposure scenario**

- **Short title of the exposure scenario**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9b Fillers, putties, plasters, modelling clay
- **Process category** PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
- **Article category** AC1 Vehicles
- **Environmental release category** ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Avoid contact with the skin.
Do not breathe gas/vapour/aerosol.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- **Technical protective measures**
Ensure that suitable extractors are available on processing machines
Provide explosion-proof electrical equipment.
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes.
Pregnant women should strictly avoid inhalation or skin contact.
Tightly sealed goggles
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Measures for consumer protection**
Ensure adequate labelling.
Observe consumer information and advice on safe use.

Continue on page 13

AU

Trade name: BODY F217 FIBERLIGHT POLYESTER FILLER**· Environmental protection measures**

- **Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.
- **Soil** The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** This product is to be used by professional technicians only.
- **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.



Auto Refinishing Products

Page 1/11

Printing date: 27.11.2023

Revision date: 27.11.2023

Version no. 1

Safety Data Sheet
according to WHS Regulations

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

Product identifier

· Trade name: **BPO PASTE HARDENER**

· Article number: 11202

· Relevant identified uses of the substance or mixture and uses advised against

· Life cycle stages F Formulation or re-packing

· Sector of Use

SU9 Manufacture of fine chemicals

SU12 Manufacture of plastics products, including compounding and conversion

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

PC7 Base metals and alloys

PC9b Fillers, putties, plasters, modelling clay

· Process category

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Technical function Catalyst

· Application of the substance / the mixture Surface protection

Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Continue on page 2

AU

Trade name: **BPO PASTE HARDENER**

- Further information obtainable from:
Sydney Automotive Paints & Equipment PTY LTD
Unit A3, 366 Edgar St. Condell Park NSW 2200
AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001
- Emergency telephone number:
If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zealand 0800 764 766.

* **2 Hazard(s) Identification**

· **Classification of the substance or mixture**



Serious eye damage/irritation – Category 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

· **Label elements**

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS07



- Signal word Warning
- Hazard-determining components of labelling:
dibenzoyl peroxide (50-<60 %)
- Hazard statements
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- Precautionary statements
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

* **3 Composition and Information on Ingredients**

· **Chemical characterisation: Mixtures**

- Description: Mixture of hazardous substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 94-36-0	dibenzoyl peroxide	50-<60%
EINECS: 202-327-6	 Self-react. B, H241; Org. Perox. B, H241	
Index number: 617-008-00-0	 Serious eye damage/irritation – Category 2A, H319; Skin Sens. 1, H317	
RTECS: DM 8575000		

Continue on page 3
AU

Trade name: BPO PASTE HARDENER

CAS: 107-21-1 ethanediol
 EINECS: 203-473-3 ⚠ Acute Tox. 4, H302
 Index number: 603-027-00-1
 RTECS: KW 2975000

5-<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· Most important symptoms and effects, both acute and delayed No further relevant information available.
· Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Hazardous decomposition products**
In case of fire it is possible that the following substances are released:
Carbonic Anhydride
Carbon Monoxide
Benzene
Bophenyl
Phenyl Benzoate
Under certain conditions the presence of other toxic substances cannot be excluded
- **Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **Special protective equipment and fire fighting procedures:** No special measures required.
- **Additional information**
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

Continue on page 4
AU

Trade name: BPO PASTE HARDENER

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* **7 Handling and Storage**

- **Handling:**

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about fire - and explosion protection: Prevent impact and friction.

- **Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements.

- Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.

- **Specific end use(s)** No further relevant information available.

* **8 Exposure controls and personal protection**

- **Additional information about design of technical facilities:** No further data; see section 7.

- **Ingredients with limit values that require monitoring at the workplace:**

107-21-1 ethanediol

WES Short-term value: 104** mg/m³, 40** ppm

Long-term value: 10* 52** mg/m³, 20** ppm

Sk;*particulate;**vapour

- Additional information: The lists valid during the making were used as basis.

- **Personal protective equipment:**

- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 5

AU

Trade name: BPO PASTE HARDENER

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and Chemical Properties**General Information**

- Appearance:
- Form: Pasty
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- **pH-value:** Not determined.
- **Change in condition**
- Melting point/freezing point: Undetermined.
- Initial boiling point and boiling range: 197 °C
- **Flash point:** Not applicable.
- **Flammability (solid, gas):** Not applicable.
- **Autoignition temperature:** 555 °C
- Decomposition temperature: Not determined.
- **Ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product does not present an explosion hazard.
Risk of explosion by shock, friction, fire or other sources of ignition.
- **Explosion limits:**
- Lower: Not determined.
- Upper: Not determined.
- **Vapour pressure at 20 °C:** 1 hPa
- **Density at 20 °C:** 1.2528 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- **Solubility in / Miscibility with**
- water: Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
- Dynamic: Not determined.
- Kinematic at 20 °C: 0 mm²/s

Continue on page 6
AU

Trade name: BPO PASTE HARDENER**Solvent content:**

- VOC (EC) X
0.0 g/l
- Solids content (volume): 50.0 %
- **Other information** No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information**Information on toxicological effects**

- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

131-11-3 dimethyl phthalate

Oral LD50 6,800 mg/kg (rat)

Dermal LD50 >10 mg/kg (rabbit)

107-21-1 ethanediol

Oral LD50 5,840 mg/kg (rat)

Dermal LD50 9,530 mg/kg (rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

12 Ecological Information**Toxicity****Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

Behaviour in environmental systems:

- **Bioaccumulative potential** No further relevant information available.

Trade name: **BPO PASTE HARDENER**

- Mobility in soil No further relevant information available.
- **Additional ecological information:**
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- ADG, IMDG, IATA UN2810
- **UN proper shipping name**
- ADG UN2810 TOXIC LIQUID, ORGANIC, N.O.S. (dimethyl phthalate), ENVIRONMENTALLY HAZARDOUS
- IMDG TOXIC LIQUID, ORGANIC, N.O.S. (dimethyl phthalate, dibenzoyl peroxide), MARINE POLLUTANT
- IATA TOXIC LIQUID, ORGANIC, N.O.S. (dimethyl phthalate)
- **Transport hazard class(es)**

- ADG



- Class 6.1 (T1) Toxic substances.
- Label 6.1
- IMDG



- Class 6.1 Toxic substances.
- Label 6.1

Trade name: BPO PASTE HARDENER

· IATA



· Class	6.1 Toxic substances.
· Label	6.1
· Packing group	
· ADG, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: dibenzoyl peroxide
· Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADG):	Symbol (fish and tree)
· Special precautions for user	Warning: Toxic substances.
· Hazard identification number (Kemler code):	60
· EMS Number:	F-A,S-A
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADG	
· Limited quantities (LQ)	100 ml
· Excepted quantities (EQ)	Code: E4 Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	100 ml
· Excepted quantities (EQ)	Code: E4 Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2810 TOXIC LIQUID, ORGANIC, N.O.S. (DIMETHYL PHTHALATE), 6.1, II, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

2X

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· Australian Inventory of Industrial Chemicals

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

94-36-0 dibenzoyl peroxide: S2, S4, S5

131-11-3 dimethyl phthalate: S10

107-21-1 ethanediol: S5, S6, S10

Continue on page 9
AU

Trade name: BPO PASTE HARDENER

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS07

- Signal word Warning
- Hazard-determining components of labelling:
dibenzoyl peroxide (50-<60 %)
- Hazard statements
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- Precautionary statements
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES
E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H241 Heating may cause a fire or explosion.
H302 Harmful if swallowed.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**
HB BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033
email: stamkou@hbbody.com
- * Data compared to the previous version altered.

Trade name: **BPO PASTE HARDENER**

Annex: Exposure scenario

Short title of the exposure scenario

· Sector of Use

- SU9 Manufacture of fine chemicals
- SU12 Manufacture of plastics products, including compounding and conversion
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category

- PC7 Base metals and alloys
- PC9b Fillers, putties, plasters, modelling clay

· Process category

- PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Article category AC1 Vehicles

· Environmental release category ERC2 Formulation into mixture

· Technical function Catalyst

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

· Duration and frequency

- 5 workdays/week.
- Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· Physical state Fluid

· Concentration of the substance in the mixture The substance is main component.

· Used amount per time or activity Smaller than 0.5 kg per application.

Other operational conditions

· Other operational conditions affecting environmental exposure

- No special measures required.
- Use only on hard ground.

· Other operational conditions affecting worker exposure

- Avoid contact with eyes.
- Avoid contact with the skin.
- Avoid long-term or repeated skin contact.
- Keep away from combustible material.
- Take precautionary measures against static discharge.
- Keep away from sources of ignition - No smoking.

· Other operational conditions affecting consumer exposure No special measures required.

· Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

· Worker protection

· Organisational protective measures

- No special measures required.
- Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

- Ensure that suitable extractors are available on processing machines
- Provide explosion-proof electrical equipment.
- Use product only in enclosed systems.

Trade name: BPO PASTE HARDENER**· Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures**· Water**

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· Disposal measures

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste type Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.